





ETON PFX SERIES - POWERFUL COAXIAL SYSTEMS

The coaxial systems of the ETON PFX series impress with their excellent tonal balance and crisp bass reproduction. The 2-way sound systems are particularly easy to install and can be used as a front system or as a rear fill.

The bass-midrange drivers feature the typical ETON powder-coated metal basket in a torsion-resistant, flow-optimized double strut design with large ventilation openings. Strong ferrite magnets provide power and dynamics. Thanks to 3 ohms technology, the coaxial speakers are extremely efficient – even with a standard radio/head unit, without an additional amplifier.

Top sound in the entry-level class: The cone of the mid/woofers consist of a rib-reinforced paper/glass fiber mixture – produced in a special manufacturing process. This increases the volume without changing the weight. In addition, rib reinforcements are pressed into the material. The cone is therefore particularly light and extremely rigid: the best prerequisites for an impressive sound performance with powerful, dynamic bass.

In combination with the integrated 25 mm (PFX 16) or 19 mm (PFX 13, PFX 10) fabric dome tweeters, a perfect unit is created for outstanding sound – silky smooth and with the necessary brilliance

and fine dynamics. The open design of the tweeter's touch protection ensures maximum sound transmission – especially when the tweeters are mounted behind the original cover grilles.

The long-distance tuning with the necessary fun factor make the PFX coaxials easy-to-install sound systems with an impressive price-performance ratio!

KEY FEATURES ETON PFX COAXIALS

- Newly developed rib-stiffened paper-fiberglass cone
- Powder-coated metal basket with large ventilation openings
- Powerful ferrite magnet with large pole core bore
- 3 ohms impedance for particularly high efficiency
- Integrated 25 mm/1" (PFX 16) or 19 mm/3/4" (PFX 13, PFX 10) tweeter
- Tweeter with fabric dome and newly designed touch protection
- Engineered in Germany
- Scope of delivery: 2 x coaxial speakers, drilling template,
 2 x Gravoxal plate with ETON logo, incl. screws and sheet
 metal nuts







TECHNICAL DATA	PFX 10 · 10 cm / 4"	PFX 13 · 13 cm / 5"	PFX 16 · 16.5 cm / 6.5"
Nominal / Music power handling	50 W RMS / 80 W	60 W RMS / 90 W	70 W RMS / 100 W
Impedance	3 ohms	3 ohms	3 ohms
SPL	91 dB	92 dB	93 dB
Outer Ø	110 – 124 mm	132 – 147 mm	165 mm
Mounting Ø / Mounting depth	91 mm / 45 mm	113 mm / 57 mm	142 mm / 66 mm