



HIGH PERFORMANCE 6 MM² POWER CONNECTION CABLE KIT

The high-quality 6 mm² power connection cable set PCC 6 (AWG 10) contains everything you need to easily connect an amplifier or an active subwoofer – perfectly cut to length and put together in a smart set. Engineered in Germany!

The kit includes a 5.5 m long, highly flexible, PVC-coated, fine-stranded, 100% OFC oxygen-free 6 mm² power cable made of solid copper, B+, and a matching 1 m long 6 mm² GND-cable with the same specification. A pressed-on ring lug in the appropriate size with insulation makes installation easier and saves installation time. The special PVC jacket coating simplifies cable installation and protects the cables from cuts and breaks.

5.5 m remote cable in 0.75 mm² (AWG 19) including matching wire-end ferrule and crimp connector for 0.5 – 1.5 mm² cable is included in the kit. The kit also includes a cable branch connector for 0.5 – 6 mm² (AWG 22 – 18) – making the installation of an amplifier, active subwoofer or other electronic devices child's play.

Two ring terminals and two fork shoes with red and black insulation are also included in the kit. Four wire end ferrules, an AFS fuse holder and two ATC fuses (20 A) are also included, as well as an Allen key, cable ties and strongly adhesive Velcro tape for installation.

SET CONTENT

- 5.5 m 6 mm² high performance power cable, fine-stranded 100% OFC oxygen free solid copper cable, B+, red with pressed-on ring lug, soft PVC jacket and special coating for easy installation of the cables inside the vehicle with high protection against kinks and breaks
- 1 m 6 mm² high performance power cable, fine-stranded 100% OFC oxygen free solid copper cable, GND-, black with pressed-on ring lug, soft PVC jacket and special coating or easy installation of the cables inside the vehicle with high protection against kinks and breaks
- 5.5 m power-on remote cable 0.75 mm² / AWG 19, blue, incl. matching wire-end ferrule, gold
- Waterproof, modern AFS fuse holder for Mini ATC fuses (up to 40 A) with matching allen key
- 2 x ATC fuse 20 A
- 4 x wire-end ferrule 6 mm² / AWG 10, gold plated
- 2 x ring terminal 6 mm² / AWG 10, M6 (red + black insulation)
- 2 x fork shoes 6 mm² / AWG 10 (red + black insulation)
- Crimp connector plug pair: 0.5 – 1.5 mm², red
- Cable branch connector for 0.5 – 6 mm² / AWG 22 – 18
- 8 x cable ties, 3 x 100 mm, black
- Strongly adherent, self-adhesive Velcro tape